



## Infrared Lighting/Heating Bridge

### Optimum Warm Keeping and Illumination of Arranged Dishes

#### Warm Plates for Content Guests

Every chef has incurred the problem that, during rush hours, their service people may need some more time to bring the plates to the guests' tables – meaning that the carefully arranged dishes are delayed at the pass for a few moments before they can be served to the guests.

To ensure that every guest gets their dish warm and at its best in order to enjoy the chef's culinary art regardless of heavy traffic at the pass, Beer Grill have developed the infrared lighting/heating bridge that keeps plates with arranged food warm in an optimum way. Matching lighting channels are also available, providing optimum illumination that can be of great advantage when arranging food on the plates.

The infrared lighting/heating bridge is available in single-row and double-row models in various sizes. The heat is generated by ceramic heating elements.

#### Further advantages

- ❑ Available in single- or double-row models for one or two plates in line
- ❑ A variety of channel lengths: 670 / 920 / 1,262 / 1,512 / 1,762 / 2,104 / 2,354 mm for 2 - 7 plates side by side
- ❑ Single-row versions with 800 / 1,200 / 1,600 / 2,000 / 2,400 / 2,800 or 3,200 watts
- ❑ Double-row versions with 1,000 / 1,500 / 2,000 / 2,500 / 3,000 / 3,500 or 4,000 watts
- ❑ Stainless steel housing
- ❑ Control by heat-proof revolving switch on the right- or left-hand side
- ❑ Protective guard below the heating elements
- ❑ Side panels prepared for the installation of accessories and consoles
- ❑ Independent controls for lighting and heating
- ❑ Wide range of dedicated accessories for installation and configuration
- ❑ The heating channel of the larger models is divided into up to three zones



# Infrared Lighting/Heating Bridge




## The range


- Lighting/heating bridges in single- and double-row versions
- Various supports and consoles for installation above tables or suspended from ceilings or walls
- Range of standard sizes in lengths from 670 to 2354 mm
- Individual switching of lighting and heating by heat-proof revolving switch

## Examples of console types and mounting brackets


Standard console for non-fixed installation with central support




Standard console for fixed installation with central support




Standard console for fixed installation with rear support



Suspended console with central support




Bracket for suspended installation




Please contact your sales partner for further details

## Applications for heating bridges


Single-row



Double-row



Double single-row



Food perfectly presented **BEER**

Beer Grill AG  
Allmendstraße 7  
CH-5612 Villmergen

Tel. +41 (0)56 618 7800  
Fax +41 (0)56 618 7849

Beer Grill GmbH  
Körnerstrasse 14a  
D-79539 Lörrach

Tel. +49 (0)7161 659 876  
Fax +49 (0)7161 659 879

info@beergrill.com  
www.beergrill.com