



NEW WITH
LED
LIGHTING



Solaris

Solaris - Design Light/Heat Bridge for perfectly-presented dishes

Flexibility and variety

Use of the modern Solaris light/heat bridge ensures perfect illumination of your dishes on offer and heat from above. This combines innovative design and the highest quality with top-quality materials and pioneering technology.

Diverse deployment and combination possibilities

Solaris can be deployed to save space independent of the presentation area and structural circumstances. It can be individually used in combination with hotplates, mobile table devices and also in combination with built-in devices. The many combination possibilities of light and heat provide optimal illumination of your culinary skills.

Your benefits

- Heat radiation from above with high-performance infrared radiators
- Warming light dimmable (option)
- Perfect presentation with powerful LED lighting
- Modern design
- Diverse deployment options
- Swift erection or simple assembly thanks to numerous supports and assembly fixtures
- Double or single channels with various equipment depending upon use and requirement
- Hygiene requirements fulfilled by breath protection
- Large selection of standard sizes, special sizes to suit customers' requirements available on request
- With optional coat of paint to match your colour concept
- Warm- and neutral light with anti-splinter cover

Food perfectly presented

BEER



Solaris - perfectly suitable for every concept



The range

- ▣ Solaris with individual or double channel (only neutral light, only warming light or both in combination)
- ▣ Various supports and consoles for table-top, ceiling or wall fitting
- ▣ Supports and consoles in right-angled tube (right-angled tube; adjustable for height or fixed)
- ▣ As plug-in device (T12 or Schuko plug) or fixed connection
- ▣ Breath protection in ESG safety glass on guest's side or both sides
- ▣ Divider shelf to suit Solaris individual or double channel
- ▣ Colour painting to customers' requirements
- ▣ Diverse standard sizes with a length of 598 to 2128 mm, special lengths to suit customers' requirements upon request



Solaris for free-standing



Solaris for mounting on ceilings






Solaris for table-top mounting



Solaris for wall-mounting



Solaris for mounting on the face side



Individual channel

- ▣ Individual channel with warming light (IR radiator 300 W per GN)
- ▣ Individual channel with neutral light (LED)
- ▣ One on/off switch each

Double channel

- ▣ Double channel with warming light or warming/neutral light with switching function
- ▣ Neutral light with on/off switch
- ▣ Warming light on/off switch or selectively with dimmer